ClearTouch MEDIA

ClearTouch MEDIA

CONTENTS

Video Wall Controller Series

TV Wall Controller 01

FDMC Series UHD Video Wall Controller 03

Matrix Switcher Series

FDMA Series UHD Mixed Matrix Switcher 05

FDMA Series Network Digital Matrix Switcher 07

FDMB Series UHD Seamless Matrix Switche 09

IP Distributed System

IP Distributed System 11

Media Player

Digital Network Player 13

HD-BaseT

HD-baseT Extender 14

Video Wall And Digital Signage

Video Wall 15

Ultra Thin Double Sides Advertising Player 16

Digital Advertising Player Kiosks 17

Advertising Player 18

TV Wall Controller

TV wall controller is an HD picture splicing video controller specially designed for LCD TVs, ultra-narrow bezel LCD screens and projectors. According to user needs, 4,6,9,and 12 channels of HDMI output can be customized, and unlimited splicing can be customized through the cascade. The product uses high-definition processing chips to support the input and output of 1080P signals. Supports one composite video, one VGA, one USB, one DVI, and one HDMI input at the same time, all input signals can be switched to large screens for splicing display, and audio and corresponding video are output synchronously. In order to make it more simple and intuitive when operating the splicing processor, the product is designed with infrared remote control, chassis button control, and can also be controlled by RS-232. The user can perform one-click quick control and full-function control on the splicer through buttons or remote control, so that the operation is more humanized and simpler.

Functional characteristics

1 Splicing modes:
The TV wall controller adopts a modular design , which can increase or decrease output modules according to user requirements. A single machine can achieve a maximum of 4,6,9,12 HDMI signal splicing outputs, and is compatible with the DVI1.0 protocol, achieving unlimited number of splicing through cascades. According to user' s requirements, a single machine can be customized with 2x2, 3x3, 1x2, 1X3,2x3, 3x2, 2x4, 4x2, 2x5, 5x2, 3×4, 4×3 and other splicing modes.

2 Input/output signal
Supports 1 composite video, 1 VGA, 1 DVI, 1 HDMI, 1 USB total four signals input, HDMI and USB signal interface comes with audio decoding, composite video and VGA signals plus the corresponding binding audio Interface, all input video signals can be synchronized with audio output switching.

2×2

2×3

3×4

Technical specifications

Name	Specification		
Model	FM-1804	FM-1806	FM-1809
Output Port	4xHDMI	6xHDMI	9xHDMI
Input Port	1×VGA 1×HDMI 1×DVI 1×USB		
Splicing scale	2×2, 1×2, 1×3	2×3, 3×2, 2×2	3×3, 2×4, 2×3
Size	207.6×186.6×44.45mm	360mm×160mm×45mm	360mm×160mm×45mm
control method	Infrared remote control, front panel keys.		
Power supply	DC 12V - 3A		
Power	50w		
Recommended maximum input distance	When Less than 30 meters, at 1920x1080@60hz,recommend to use certified hdmi special wire		
Recommended maximum output distance	When Less than 20 meters, at 1920x1080@60hz,recommend to use certified hdmi special wire		
Type of control	Serial control, button, remote control		
Baud rate and protocol	Baud rate:9600,Data bits:8,Stop bit:1,No parity		
Temperature	-20°c - 70°c		
humidity	10% - 90%		
Average time between failures	30000H		

FDMC SERIES UHD Video Wall Controller

Functional characteristics

1. Using High speed data transmission technology with full crossover scheduling architecture
2. Each data channel is set with point to point special data channel, keep real time display
3. Support splicing frame effect adjustment, window fade-in fusion
4. Video windows can be roamed, superposed, zoomed, spliced and used flexibly freely
5. Hot pluggable structure, high integration of chassis, multi windows picture in picture, picture out picture
6. Advanced software design, Multiple plans round play function
7. Support network control, RS232 control Multiple plans round play function
8. Pure hardware structure, no operating system, high stability

Video wall controller is a pure hardware, professional, high-performance, high-end image processing equipment. It can display multiple dynamic images on multi screen in real time without losing frames to realize the function of multi window splicing.It is mainly applied to high quality, high definition large screen splicing display system. It is the core control device of the system display, and provides an ideal image processing solution for the application of command center, video conference, multi-media hall and other places.

The video wall controller adopts large-scale high-performance FPGA array and high-speed digital switching technology architecture, combined with full digital hardware design concept, and realizes CPU free operation system of video and image processing workstation. video wall controller has powerful processing capabilities, such as broadband video signal acquisition, real-time high resolution digital image processing, 3D higher-order digital filtering and other high-end image processing functions. The controller uses digital multi bus paralleling and digital multi bus data switching processing mechanism, which can fundamentally ensure all the input signal sources are with real-time processing and data consistency, without delay, no discretization , and no frame loss of the image

Technical specifications

Type	Project	Paremeter			
Host paremeter	Case specification	1.5U	3U	5.5U	9U
	Control panel	1	1	1	1
	Input slot	2	4	8	16
	Output slot	2	4	8	16
	Size(mm)(L)*(W)*(H)	482.6*387.5*72	482.6*387.5*138	482.6*403*240	482.6*403*383
Board parameter	Input card	Multiple input cards can be free combinated:VGA, DVI, HDMI, SD/3G/HD/SD-SDI, RJ45, YPbpr/ YCbcr etc. 4 interface per input card			
	Output card	DVI/HDMI 2 interface per output card			
	Support maximum resolution	3840*2160@30HZ			
	Display mode	Multi- picture- equivalent image display			
	Input distance	≤10m (AWG26 HDMI1.4 cable standard)			
	Output distance	≤10m (AWG26 HDMI1.4 cable standard)			
Control parameter	Processor manage ethernet port	1* RJ-45 port, 10/100M self-adaption, support management and configuration of communication processor			
	Processor manage serial port	2* RS-232 ports, support controlling of outreach matrix, screen and other third party devices			
Function parameter	Transmission belt weight	6.75Gbps			
	Output resolution	3840*2160@60			
Software parameter	Control software	PWController apply to WindowsXP/Vista/WIN7			
Environmental parameter	Working temperature	-10℃ - 60℃			
	Working humidity	5~95% no cooling			
	Maximum power(W)	300W			
	Electrical characteristics	Input 165~240V AC, pluggable power supply			

Schematic diagramcifications

FDMA SERIES UHD Mixed Matrix Switcher

Flowvia UHD mixed matrix switcher is a high-performance UHD video signal switching device, which is compatible with digital and analog signal input, and support multi-format signals. Output of any signal can choose the signal source freely without disturbing other output, minimize the attenuation of signal transmission, image and sound signal can be outputted with high fidelity. Our matrix switcher has functions such as breaking electric field protection, LCD and multi-format signals switched, which is with card inserted structure, and support signal input such as HDMI, DVI, Video, VGA and Ypbpr, and HDMI signal output. At the same time, it also has network and RS232 communication interface, which can be used easily by personal computer and control equipment. The device provides a new solution for the professional project that needs digital, audio and video switching.

Functional characteristics

1. Support CVBS, YPbPr, VGA, SDI, HDMI, DVI etc signal sources input.
2. Support HDMI 1.4/ 1.3 version, HDCP1.4 and DV1.0 standard.
3. Support EDID automatic management, ensure every signal source present the best effect.
4. Support plan looping play function , can set looping play switch, looping play time and the channel etc.
5. Supply 16 plans, can save and call the plan at anytime, and one-key switch to the saved display condition.
6. Automatic save and switch to the display condition before power off
7. Support 1.5U/ 3U/ 5U cases, apply to 19 inch cabinets.
8. Support LCD display, switching easily between Chinese and English.
9. Support panel, remote control, RS-232, RJ-45, IPad etc methods of management .
10. With signal indicator light, monitor the signal condition of input and output conveniently.
11. HDMI output supports independent audio socket output. (option)
12. Support Authorized encryption design. can set matrix usage time
13. Support automatic balance of long-cable output up to 20 meters.
14. Using card inserted case, whole modular design, Flexible configuration and upgrade easily.

Technical specifications

Type	Project	Paremeter				
Host paremeter	Case specification	1U	1.5U	3U	5.5U	9U
	Control panel	1	1	1	1	1
	Input slot	1	2	4	8	16
	Output slot	1	2	4	8	16
	Size(mm)(L)*(W)*(H)	482.6* 230* 43.6mm	482.6* 387.5* 72mm	482.6* 387.5* 138mm	482.6* 403* 240mm	482.6* 403* 383mm
Board arameter	Input card	Multiple input cards can be free combinated:VGA, DVI, HDMI, SD/3G/HD/SD-SDI, RJ45, YPbpr/ YCbcr etc.				
	Output card	DVI, HDMI				
	Support maximum resolution	3840 X 2160 @30 Hz				
	Support audio format	DTS-HD/ Dolby- true HD/ LPCM 7.1/ DTS/ Dolby- AC3/ DSD				
	Transmission distance	Not less than 20 meters, according to cable quality when on 1920 X 1200 @60				
Control parameter	Processor manage ethernet port	1* RJ-45 port, 10/100M self-adaption, support management and configuration of communication processor				
	Processor manage serial port	2* RS-232 ports, support controlling of outreach matrix, screen and other third party devices				
Function parameter	Transmission belt weight	Single channel 10.2 Gbps				
	Output resolution	Maximum support 3840* 2160(downward compatible), can be customized				
Software parameter	Control software	MATRIX 1.0, apply to Windows XP/ Vista/ WIN 7				
Control parameter	Working temperature	-10°C~ 60°C				
	Working humidity	5~95% no cooling				
	Maximum power(W)	300 W				
	Electrical characteristics	Input 100~240V AC, can automatic adjust the power, frequence 50~ 60Hz, N+1 redundance configurable				

FDMA SERIES Network Digital Matrix Switcher

The network multi-screen image processing system is a high-definition digital decoding matrix integrated management platform independently developed and produced. The front end (network camera ICP, NVR, PC, etc.) enters the monitoring center through a network transmission system such as optical fiber. Then uniformly manage, decode, display, and splice video wall in full-screen, split it in multi-screen , superimposed roaming. Applicable to video stream coding security monitoring center, decoding access, output preview, flexible picture combination,Fast switching, timing round patrolet, diverse plans.

Functional characteristics

1. Safe and stable operation with embedded LINUX system
2. Plug-in structure for easy expansion and maintenance
3. Support network camera hybrid decoding with different resolutions of different brands
4. IP address of the IP camera can be manually added and automatically searched , and the number of connected IPC can reach more than 60,000(optinoal).
5. Add a port number with a fixed IP or domain name to access the remote webcam video.
6. Compatible with RTP, RTSP, ONVIF, H.264, H.265 and other protocol cameras and Spherical camera
7. Support powerful hard decoding capability, single card supports up to 32 channels, supports 4 channels of 1080 simultaneous decoding output
8. The display layout is flexible and diverse, and each screen image can be switched in any group of 16 groups. When switching, the image display has no delay, no jam, and the switching speed is fast.
9. After the network disconnection is restored, the video is automatically reconnected, automatically replied, and various plan combinations
10. Character ID display function, which can select the decoded image zoom according to the ID number intelligent control.
11. Support remote data collection to echo IP images, and remote control, and mobile APP intelligent control

Technical specifications

Type	Item	Parameters
Host parameters	Case size	Standard 2U case
	Case structure	Plug-in structure for easy expansion and maintenance
	Size(mm)(L)*(W)*(H)	482.6*310*72*130
Board parameters	Output interface	HDMI
	Decoding ability	H.264, H.265, 32*D1, 8*720P, 4*1080P
	Displa mode	Multiple-screen flexible segmentation image(1/4, 1/6, 1/9, 1/12, 1/16) Video output comes with splicing, window opening, superimposed roaming display
	Decoding broadband	1 screen = 5 megapixels 8 Mbps, 4 screens=1.3 million pixels 6 Mbps, 9/16 screens=D1 and the next pixel
	Decoding protocol	Support mainstream video server, DVR, NVR, Samsung, Sony, Haikang, Dahua, Yaan, Honeywell, Bosch, Tiandy , etc. ONVIF network protocol real-time dual stream preview and playback
	IPC management	Manually add and automatically search the IP address of the IP camera, and the number of IPCs accessed can reach more than 60,000 (depens on project requirements)
Environment parameters	Round plan	Switching screens by group, multiple-screen automatic round play, single-screen automatic round play, multiple sets of scene memory functions, can automatically play multiple scenes
	Upgrade	Online upgrade through PC tools
	Image response speed	Switch from camera or dome A to camera or dome B. Display speed is less than 1 second.
	Network interface	RJ45 10M/100M/1000Mbps adaptive Ethernet port
	Working temperature	-10℃~ 60℃
	Working humidity	5 ~ 95% No condensation
	The biggest power	≤180W
	Electrical characteristics	Input 110-220V AC, configurable N+1 redundancy

FDMB SERIES UHD Seamless Matrix Switcher

Flowvia UHD seamless matrix switcher, the biggest feature of the matrix is that natural black field (normal 2_10s) will not appear as in the traditional matrix in all output switching processes, achieve the true sense of the seamless switching matrix. Input and output are modular design, meet the maximum configuration, more conducive to maintenance.
It supports a variety of signals input, and all input and output can be switched seamlessly and arbitrarily. The matrix uses touch control, RS232/LAN and other ways to facilitate users to connect with other control systems. The device works continuously in 7*24 hours, thereby ensure the product's stability. There are 8*8/ 16*16/ 32*32/ 64*64 four types by now, OEM of other types are welcome.

Functional characteristics

1. Eliminate the inherent black field in the traditional matrix switching process and realize true seamless handover
2. Support CVBS, YPbPr, VGA, SDI, HDMI, DVI and other signals input
3. Support for HDMI1.4/1.3 version, HDCP1.4 and DVI1.0 standard
4. Support EDID automatic management to ensure that every channel signal presents the best effect.
5. Support image splicing display, and turn the two function matrix and splicing into one (optional)
6. Support plan looping play function , can set looping play switch, looping play time and the channel etc.
7. Supply 16 reserved plans, can save and call the plan at anytime, and one-key switch to the saved display condition.
8. Automatic save and switch to the display condition before power off
9. Support LCD display
10. Support Tablet, mobilephone, remote control, RS-232,RJ-45 etc methods of management
11. With signal indicator light, monitor the signal condition of input a nd output conveniently
12. HDMI output supports independent audio socket output.
13. Support authorized encryption design, can set matrix usage time
14. Support automatic balance of long-cable output up to 20 meters.
15. Using card inserted case, whole modular design, Flexible configuration and upgrade easily.
16. Support 1.5U/ 3U/ 5U cases, apply to 19 inch cabinets.

Technical specifications

Types	Projects	Parameters			
CPU parameters	Case specifications	1.5U	3U	5.5U	9U
	Control panel	1	1	1	1
	Input slot	2	4	8	16
	Output slot	2	4	8	16
	Size(mm)(L*W*H)	48.6*387.5*72mm	482.6*387.5*138mm	482.6*403*240mm	482.6*403*240mm
Board card parameters	Input card	Multiple input can be freely combined: VGA, DVI, HDMI, SD/3G/HD/SD-SDI, CVBS, Ypbpr/Ycbcr etc.			
	Output card	DVI, HDMI			
	Maximum support resolution	3840*2160@30Hz			
	Support audio format	DTS-HD/Dolby-trueHD/LPCM7.1/DTS/Dolby-AC3/DSD			
	Transmission distance	Not less than 20 meters, according to cable quality when 1920 X 1200 @60			
Control parameters	Processor management network port	1* RJ-45 port, 10/100M self-adaption, support management and configuration of communication processor			
	Processor management serial port	2* RS-232 ports, support controlling of outreach matrix, screen and other third party devices			
Function parameters	Transmission bandwidth	Single channel 10.2 Gbps			
	Output resolution	Maximum support 1920* 1080(downward compatible), can be customized			
Software parameters	Control software	MATRX 1.0, apply to WindowsXP/Vista/WIN7			
Environment parameters	Working temperarure	-10～60℃			
	Working humidity	5%-95% no cooling			
	Maximum power(W)	300W			
	Electrical characteristics	100-240V AC input,can automatic adjust the power, frenquency is 50-60 Hz,			

IP Distributed System

Flownet IP distributed system is a professional high-definition network coding product. It adopts high-performance image processing technology and features low bandwidth, low delay, high definition and high stability. It can be widely used in military defense, airport air traffic control, and commercial. Display, banking finance, energy construction, education and teaching industries.

Functional characteristics

1. H.264 video compression algorithm
2. Full HD 1080P60Hz, high compression ratio, high picture quality
3. Massive access to IPC (IP Camera) signals and direct decoding on the display wall
4. Can access massively DVI/HDMI signals
5. Multi-window image real-time preview monitor display, preview each signal in advance
6. Can support ultra high definition base map and character overlay
7. Industrial quality, light and easy to install
8. The output node can realize the mixed output of multiple signals at the same time, and can realize any size zoom display and arbitrary full wall roaming (single screen, cross screen, full wall display)
9. Based on non-blocking network switch architecture, no backplane design, system with strong self-recovery ability
10. No cooling fan system design, quieter operation
11. Linux embedded operating system, safe and reliable
12. Based on super five types of CATe5 and above specifications, the transmission distance can be further

Schematic diagramcifications

Technical specifications

Item	FNet-c01 Input node	FNet-c01 Output node
Master control CPU	ARM Cortex A9 multi-core, Main frequency 1GHz and above	ARM Cortex A9 multi-core, Main frequency 1GHz and above
Data encoding format	H.264, MPEG-2/4, MJPEG	
Node memory	4Gb	4Gb
Interface	1*RJ45 output/4*DVI input	1*RJ45 output/4*DVI input
Bus bandwidth	10/100/1000Mbps Gigabit	10/100/1000Mbps Gigabit
Synchronization technology	Original graphic mosaic synchronization technology(ESYNC)	Original graphic mosaic synchronization technology(ESYNC)
Color depth	32 bits per pixel	32 bits per pixel
Resolution	Support DVI 640x480~1920x1080@60Hz input	Support DVI 640x480~1920x1080@60Hz input
Operating environment	Working temperature:-10℃~60℃	Working temperature:-10℃~60℃
	Working humidity: 5~95% No condensation	Working humidity: 5~95% No condensation

Digital Network Player

TV | Network player | AD digital screen

Functional characteristics

1. It can be combined with a veriaty of display deviced
2. It is operational as long as the display device with HDMI or video interface
3. Instantly let the display device turn into the advertising player
4. Rotate freely, display mode: video and picture can be rotated 90°/180°/270°
5. Transfer video at the same time, player connected to the TV, enjoy a lot of videos
6. Support mobile phone to play on the same screen
7. Support rolling caption and split screen
8. 2K HD Image quality resolution: 1920×1080 clear to show every detail

Technical specifications

Product parameters		
Core	CPU	RK3188 coretex-a9 quad-core 1.6ghz
	DDR	DDR-3 1GB
	NAND	Standard 8GB NAND Flash
Display	HDMI	HDMI 1.4 standard interface, up to1080P
Voice	HDMI	HDMI stereo
	Audio interface	3.5mm stereo interface
Network	Ethernet	1 10/100mbps ethernet
	Wifi	Wireless protocol 802.11 b/g/n
Interface	TF card	1 standard TF card interface with maximum support of 32G
	USB 2.0	2 USB 2.0 host interfaces
Support for all video format decoding: Mpeg-1/2, Mpeg-4, DIVX, REAL MEDIA, H.264, MVC, GOOGLE VP8, WMV9 VC1, H.263, SORENSON SPARK, ON2 VP6, MJPG, etc...		

HD-baseT Extender

This product is used by a pair of transmitter TX and receiver RX. Advanced HDaseT technology, compliant with HDMI 1.4, maximum transmission distance up to 70meters. The Full HD HDMI signal and R232 signal are transmitted by a single Cat5e/6 network cable to control the remote device. It is Widely used in high-definition conferences, video advertising, digital home, multimedia teaching, projection conferences, etc.

Functional characteristics

1. Support: HDMI1.3 standard
2. Support: point-to-point and cascading transmission
3. Standard: International 802.3 Ethernet standard
4. Transmission distance: 70 meters transmission with Cat5e/6 network cable
5. Transmission rate: 10.2Gbps page high speed duplex transmission
6. Pure hardware design, plug and play, no software required to install the amount
7. Appearance structure: exquisite appearance with hanging holes, easy to install

Technical specifications

Project	Paremeter	
Function	Transmission signal type	HDMI signal
	Transmission cable	one signal cat5e/6 network cable
	Transmission distance	70 meter cat5e/6 network cable
Power part	Power supply	DC 12V1A
	Power	transmitter<3.5w, receiver<3.5w
HDMI performance and port	Support HDMI version	HDMI 1.3
	HDMI resolution	1080p/1080i/720p/ 576p/576i/480p/480i
	Support video color format	24 bit/ 30 bit/ 36 bit/ 48 bit
	Support audio format	DTS+HD/Dolby+truel HD/ LPCM7.1DTS/Dolby-AC3/DSD
	Max transmission speed	10.2Gbps
	Output cable distance	≤5m(AWG26HDMI1.3 cable strandar)
	Input cable distance	≤5m(AWG26HDMI1.3 cable strandar)

Type	Project	Paremeter
RS232 transmission performance and port	Transmission port	3Pin screen crimping terminal
	Function	Transmitter and receiver can performdata duplex communication via RS232
Protection level	Static protection	1a contact discharge level 31b air discharge level 3
Operating environment	Operating temperature	-20~60℃
	Storage temperature	-20~80℃
	Temperature (no condensation)	5~80℃ condensation
Body attribute	Size (length × width × height)	106mm /94.5mm/26.mm
	Color	Black
	Mean time between failures	>40000H

Schematic diagramcifications

Video Wall

Technical specifications

Parameter					
Specification	Panel brand	SAMSUMG		LG	
	Screen Size	46 inch	55 inch	49 inch	55 inch
	Resolution	4000:1		1400:1	
	Brightness(Max)	500cd/m² / 700cd/m² / 500cd/m²		500cd/m² / 700cd/m² / 800cd/m²	
	Bezel	1.7/3.8/5.5		1.7/1.7H/3.5	
	Contract Ratio	1920×1080			
	Operating System	Single version			
video / Images	Supported Formats	RM/RMVB, MKV, TS, FLV, AVI, VOB, MOV, WMV, MP4, BMP, JPEG, PNG, GIF			
	Input Optional	Input port: VGA, DVI, HDMI, RJ45			
Audio	Built-in Loudspeaker	2*8Ω5W			
Communication	Wifi	Optional			
	Touch Screen	Optional			
	3G-4G Modem	Optional			
General Information	Input Voltage	110-240V AC			
	Certifications	CE, RoHS, ISO9001			

Ultra Thin Double Sides Advertising Player

3rd Generation LG original screen , laminate the screen to the glass with laminating technology, you will see it is dark black when turn off the screen.

Technical specifications

Size	55 inch	49 inch	43 inch
Resolution	3840×2160	3840×2160	3840×2160
Brightness	450cd/m*2		
Contrast	4000:1		
Backlits	LED		
Response time	6.5MS		
Color	16.7M		
Viewing angel	178°/178° (H/V)		
Aspect ratio	16:09		
CPU	Quard core Cortex A72 2GHz		
Mainboard	RK3288		
GPU	Quard core ARM Mali-T764 MP		
RAM	DDR3 2GB		
ROM	EMMC 16GB		
Storage	TF/USB		
Display	Rotate, two screen display same, two screen display different		
IO connectors	INPUT:2×USB, 2XHDMI, TFX1, LANX1,SATAX1 / OUTPUT:SIGNAL DISPLAYX2, IR REMOTE CONTROLLERX1, AUDI 10WX2 SPEAKER		
Wired network	Built-in Realtek RTL8103EL		
Audio	Built-in HD audio 8 (Realtek ALC888) audio system		
Video format	WMV, AVI, FLV, RM, RMVB, MPEG, TS, MP4, Audio:MP3		
Photo format	JPG, JPEG, BMP, PNG, GIF		
OS	Android 7.1		
OSD language	Chinese, English		
WIFI	YES		
Feature	RTC clock,tomer on/off, extend SATA hard disk		
3G/4G	Optional		
Play mode	Rapeat, Timing, Insert Play and so on		
Network	Rj45 Ethrenet, Wifi, and other wireless devuce extended		
Environment	Operating temperature: 0℃ to 40℃ / Storage temperature: -20℃ to 60℃ / Humidity: 10%-80% RH at 40℃		
Power supply	AC 100V~240V, 50/60HZ		
Consumption	175W	145W	
TFT panel grade	Imported 3rd generation A grade		
Case	Cold rolled steel with powder coating+toughened glass surface		
Spare parts	Ceiling bracket, main box, cover, wireropex2, hanging square tube, remote controller,power cable, installation guide.		

Digital Advertising Player Kiosks

Floor Stand AD Player

Horizontal AD Player

Wall Mount AD Player

Technical specifications

Item			
Name	Floor stand AD player	Horizontal AD Player	Wall Mount AD Player
Touch screen	touch screen (optional)	touch screen	touch screen (optional)
Size	43,49,55 inch	32,43,49,55 inch	22,27,43,49,55 inch
System	Android/windows version (optional)		
Color	Black, gold, silver...etc (optional)		
Wifi	yes		
TF card	yes		

Advertising Player

More series

Bar Table Style AD Player
Support OEM / ODM
Infrared touch (optional)
43/49/55 inch screen
Stand-alone/Android/windows version (optional)
black, gold, silver...etc (optional)

LCD Bus Screen
Support OEM / ODM
Infrared touch (optional)
17/19/22 inch screen (optional)
Stand-alone/Android/windows version (optional)
black, gold, silver...etc (optional)

Newspaper Holder AD Player
Support OEM / ODM
Infrared touch (optional)
22/28/32/42 inch screen (optional)
Stand-alone/Android/windows version (optional)
black, gold, silver...etc (optional)

Double sides LCD Kiosk
Support OEM / ODM
Infrared touch (optional)
32/43/47/49/55 inch screen (optional)
Stand-alone/Android/windows version (optional)
black, gold, silver...etc (optional)

Interactive Whiteboard
Support OEM / ODM
Infrared touch (optional)
46/50/55/65 inch screen
Stand-alone/Android/windows version (optional)
black ...etc (optional)

Rotating Floor Stand AD Player
Support OEM / ODM
Infrared touch (optional)
32/43/49/55/65 inch screen (optional)
Stand-alone/Android/windows version (optional)
black, gold, silver...etc (optional)

Outdoor Waterproof AD Player
Support OEM / ODM
capacitive touch (optional)
32/42/46/55/65/75 inch screen (optional)
Stand-alone/Android/windows version (optional)
black, gold, silver...etc (optional)

Outdoor AD Player
Support OEM / ODM
capacitive touch (optional)
32/42/46/55/65/75/84 inch screen (optional)
Stand-alone/Android/windows version(optional)
black, gold, silver...etc (optional)

S-Type AD Player
Support OEM / ODM
Capacitive touch (optional)
22/32/43 inch screen
Stand-alone/Android/windows version (optional)
black, white ...etc (optional)

Touch Table AD Player
Support OEM / ODM
Infrared touch (optional)
22/43/49/55 inch screen (optional)
Stand-alone/Android/windows version (optional)
black, gold, silver...etc (optional)

Product connection schematic diagram